

RIDGEPRO™ Roof Ridge Anchor

First Man Up Anchor



1 (800) 766-5291
(717)737-4398

www.SNOBLOX-SNOJAX.com



Pitch	Distance
6:12	= 22.000"
7:12	= 22.000"
8:12	= 22.000"
9:12	= 21.750"
10:12	= 21.500"
11:12	= 21.125"
12:12	= 20.750"

**Distance Between Pads
Based On Roof Pitch**
(Dimension Changes Are Nominal)

The **RIDGEPRO™ Plus** option includes a 16' Fiberglass Telescoping Pole.



This safety device is a First Man Up (FMU) Last Man Down (LMD) roof anchoring system that is designed for 6:12 to 12:12 roof pitches. The RIDGEPRO™ offers a safe solution for transitioning from the ladder to the actual roof and back to the ladder. It allows for quicker access to the peak than a standard fall protection rope and harness setup. The cross members are padded to protect your roof's finish. The body is made from super strong, lightweight, high-grade aluminum for easy transport and has a built-in stainless-steel shackle harness and rope receiver. (Does not include a rope or harness) The RIDGEPRO™ Plus option includes a 16' Fiberglass Telescoping Pole. The RIDGEPRO™ may be used temporarily for 15 minute inspections or may be permanently attached with 5/16 lag bolts to make it OSHA compliant for an anchoring device. Its versatility allows for use across a wide variety of roofing materials and is perfect for installing snow guards on just about any steep roof.